

1. Identification of the substance/mixture and of the company

Product identifier

Trade name: Universal hardener
Article number: H0060-H

1.2 Relevant identified uses of substance or mixture and not advised uses

Application: universal hardener for all NILOS cold adhesives
Uses advised against: not for private use

1.3 Manufacturer / Supplier

NILOS GmbH & Co. KG, Reisholzstr. 15, 40721 Hilden, Germany
Tel.: +49 2103 951 - 0
Fax: +49 2103 951 - 199

1.4 Emergency contact details:

Phone: +49 173 9652041
E-Mail: SDB@nilos.de

2. Possible Hazards

2.1 Classification of the substance or mixture

Flammable liquids, category 2 (H225)
Specific target organ toxicity (single exposure), category 3 (H336 (central nervous system))

Hazard icons



Danger

Hazardous components which must be listed on the label

Ethyl acetate

Hazard statements:

H225 Highly flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340 + P312 BEI EINATMEN: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor/... if you feel unwell.
P403 + P235 Store in a well-ventilated place. Keep cool.

Supplemental hazard characteristics and labeling elements:

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH204 EContains isocyanates. May produce an allergic reaction.

2.2 Other hazards

In case of hypersensitivity of the respiratory tract (asthma, chronic bronchitis), handling of the product is not recommended.

Respiratory symptoms may occur even several hours after overexposure.

Dust, vapors and aerosols are the main respiratory hazard.

This substance/mixture does not contain components at concentrations of 0.1% or higher that are classified as either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

3. Composition / information for ingredients

Type of product: Mixture

3.2 Mixtures

Tris-(p-isocyanatophenyl)-thiophosphate

approx. 28 % in Ethyl acetate

Hazardous components

Ethyl acetate

Concentration [wt.-%]: approx. 72

INDEX-No.: 607-022-00-5

EC-No.: 205-500-4

REACH Registration number: 01-2119475103-46-0017

CAS-No.: 141-78-6

Einstufung (1272/2008/CE): Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 (Central nervous system)

Tris-(p-isocyanatophenyl)-thiophosphate

Concentration [wt.-%]: approx. 27

EC-No.: 223-981-9

REACH Registration number: 01-2119948848-16-0000

CAS-No.: 4151-51-3

Classification (1272/2008/CE): Acute Tox. 4 Oral H302

Chlorobenzene

Concentration [wt.-%]: < 1

INDEX-No.: 602-033-00-1

REACH Registration number: 01-2119432722-45

CAS-No.: 108-90-7

Classification (1272/2008/CE): Flam. Liq. 3 H226; Acute Tox. 4; Inhalative H332; Skin Irrit. 2 H315; Aquatic Chronic 2 H411

Candidate List of Substances of Very High Concern for Authorisation

This product contains no substances of very high concern in concentrations where an information obligation applies (REACH Regulation (EC) No. 1907/2006, Article 59)(REACH-Verordnung (EG) Nr. 1907/2006, Artikel 59).

4. First Aid Measures

4.1 Description of first aid measures

General advice:

Polluted or soaked clothing and shoes must be immediately removed, decontaminated and disposed of.

If inhaled: Take the person to fresh air, keep warm, let them rest; if breathing difficulties occur, seek medical attention.

In case of skin contact: In the event of contact with the skin, preferably wash with a cleanser based on polyethylene glycol or with plenty of warm water and soap. Consult a doctor in the event of a skin reaction.

In case of eye contact: Hold the eyes open and rinse with preferably tepid water for a sufficiently long period of time (at least 10 minutes). Contact an ophthalmologist.

If swallowed: DO NOT induce vomiting. Wash/clean mouth with water. Medical advice is required.

4.2 Most important symptoms and effects, both acute and delayed

Notes for the doctor:

The product irritates the respiratory tract and may trigger sensitisation of the skin and respiratory tract. Treatment of acute irritation or bronchial constriction is primarily symptomatic. Extended medical treatment may be required depending on the degree of exposure and the severity of the symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

Therapeutic measures: No information available.

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Carbon dioxide (CO₂), Foam, extinguishing powder, in cases of larger fires, water spray should be used.

Unsuitable extinguishing media: High volume water jet

5.2 Special hazards arising from the substance or mixture

Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen, isocyanate vapors and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes.

Fire in vicinity poses risk of pressure build-up and rupture. Containers at risk from fire should be cooled with water and, if possible, removed from the danger area.

5.3 Advice for fire-fighters

For firefighting, self-contained breathing apparatus is required, plus a gas-tight chemical hazmat suit. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Put on protective equipment (see section 8). Ensure adequate ventilation/exhaust extraction. Keep unauthorized persons away.

6.2 Environment related measures

Do not allow to escape into waterways, wastewater or soil. If not avoidable, the authorities must be informed.

6.3 Methods and material for containment and cleaning up

Remove mechanically; cover the remainder with wet, absorbent material (e.g. sawdust, chemical binder based on calcium silicate hydrate, sand). After approx. one hour transfer to waste container and do not seal (evolution of CO₂!). Keep damp in a safe ventilated area for several days.

Spill area can be decontaminated with the following recommended decontamination solution:

- **Decontamination solution 1:** 8-10% sodium carbonate and 2% of liquid soap in water
- **Decontamination solution 2:** Liquid/yellow soap (potassium soap with ~15% anionic tenside): 20ml; Water:700ml; Polyethylen glycol (PEG 400): 350ml
- **Decontamination solution 3:** 30 % commercial laundry detergent containing monoethanolamine, 70 % water

6.4 Reference to other sections:

For further disposal measures see section 13.

7. Handling and storage

7.1 Precautions for safe handling

Provide sufficient air exchange and/or exhaust in work rooms. Exhaust ventilation necessary if product is sprayed

Solid products: Avoid formation and deposition of dust.

In all areas where isocyanate aerosols and/or vapor concentrations are produced in elevated concentrations, exhaust ventilation must be provided in such a way that the workplace exposure limits (WEL) is not exceeded. The air should be drawn away from the personnel handling the product. The threshold limit values noted in section 8 must be monitored.

Products containing solvent: Explosion protection required.

The personal protective measures described in section 8 must be observed. The precautions required in the handling of isocyanates must be taken. Contact with skin and eyes and inhalation of vapors must be avoided under all circumstances.

Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at end of work and use skin-protecting ointment. Keep working clothes separately. Take off all contaminated clothing immediately

7.2 Conditions for safe storage, including any incompatibilities

Keep container dry and tightly closed in a cool and well ventilated place. Further information on the storage conditions which must be observed to preserve quality can be found in our product information sheet.

Storage class (TRGS 510) : 3: Flammable liquids

7.3 Specific end use(s)

No information available.

8. Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Substance	CAS-No.	Basis	Type	Value	Peak limit value	Remarks
Ethyl acetate	141-78-6	EU ELV	TWA	200 ppm 734 mg/m ³		Indicative
Ethyl acetate	141-78-6	EU ELV	STEL	400 ppm 1.468 mg/m ³		Indicative
Ethyl acetate	141-78-6	TRGS 900	STEL CL			Category I: substances for which the local effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages
Ethyl acetate	141-78-6	TRGS 900				Listed
Ethyl acetate	141-78-6	TRGS 900		200 ppm 730 mg/m ³	2	Y

The product may contain traces of phenylisocyanate.

Substance	CAS-No.	Basis	Type	Value	Peak limit value	Remarks
Phenyl isocyanate	103-71-9	TRGS 900				Listed
Phenyl isocyanate	103-71-9	TRGS 900		0,01 ppm 0,05 mg/m ³	1	
Phenyl isocyanate	103-71-9	TRGS 900	STEL CL			Category I: substances for which the local effect has an assigned OEL or for substances with a sensitizing effect in respiratory passages

Derived exposure level without adverse effects

Ethyl acetate

Value type	Route of exposure	Health effects	Value	Remarks
Employee	Inhalation	Long-term systemic effects	734 mg/m ³	Most critical endpoint: Irritation (respiratory tract)
Employee	Inhalation	Acute systemic effects	1468 mg/m ³	
Employee	Inhalation	Long-term local effects	734 mg/m ³	Most critical endpoint: Irritation (respiratory tract)
Employee	Inhalation	Acute local effects	1468 mg/m ³	Most critical endpoint: Irritation (respiratory tract)
Employee	Dermal	Long-term systemic effect	63 mg/kg Bodyweight/day	
Employee	Dermal	Acute systemic effects		Not relevant.
Employee	Dermal	Long-term local effects		No quantitative risk assessment possible.
Employee	Dermal	Acute local effects		Not relevant
Consumers	Inhalation	Long-term systemic effects	367 mg/m ³	Most critical endpoint: Irritation (respiratory tract)
Consumers	Inhalation	Acute systemic effects	734 mg/m ³	

Value type	Route of exposure	Health effects	Value	Remarks:
Consumers	Inhalation	Long-term local effects	367 mg/m ³	Most critical endpoint: Irritation (respiratory tract)
Consumers	Inhalation	Acute local effects	734 mg/m ³	Most critical endpoint: Irritation (respiratory tract)
Consumers	Dermal	Long-term systemic effects	37 mg/kg Bodyweight/day	
Consumers	Dermal	Acute systemic effects		Not relevant
Consumers	Dermal	Long-term local effects		No quantitative risk assessment possible
Consumers	Dermal	Acute local effects		Not relevant
Consumers	Oral	Long-term systemic effects	4,5 mg/kg Bodyweight/day	Most critical endpoint: Irritation (respiratory tract)
Consumers	Oral	Acute systemic effects		Not relevant

Tris(p-isocyanatophenyl) thiophosphate

Value type	Route of exposure	Health effects	Value	Remarks:
Employee	Inhalation	Long-term systemic effects		No hazard identified
Employee	Inhalation	Acute systemic effects		No hazard identified
Employee	Inhalation	Long-term local effects	0,047 mg/m ³	Most critical endpoint: With repeated dose toxicity
Employee	Inhalation	Acute local effects		No hazard identified
Employee	Dermal	Long-term systemic effects		No hazard identified
Employee	Dermal	Acute systemic effects		No hazard identified
Employee	Dermal	Long-term local effects		No hazard identified
Employee	Dermal	Acute local effects		No hazard identified
Consumer	Eye contact	Local effects		No hazard identified

Chlorobenzene

Value type	Route of exposure	Health effects	Value	Remarks:
Employee	Inhalation	Long-term systemic effects	23 mg/m ³	
Employee	Inhalation	Acute systemic effects	70 mg/m ³	
Employee	Dermal	Long-term systemic effects	5 mg/kg Bodyweight/day	
Employee	Dermal	Acute systemic effects	15 mg/kg Bodyweight/day	

Predicted No Effect Concentration (PNEC)

Ethyl acetate

Compartment	Value	Remarks
Fresh water	0,26 mg/l	
Fresh water sediment	1,25 mg/kg	Dry matter
Marine water	0,026 mg/l	
Marine sediment	0,125 mg/kg	Dry matter
Sewage treatment plant	650 mg/l	
Soil	0,24 mg/kg	Dry matter
Oral	200 mg/kg	
Temporary use / release	1,65 mg/l	

Tris(p-isocyanatophenyl) thiophosphate

Compartment	Value	Remarks
Fresh water	0,1 mg/l	
Fresh water sediment	2557 mg/kg	Dry matter
Marine water	0,01 mg/l	
Marine sediment	155 mg/kg	Dry matter
Sewage treatment plant	100 mg/l	
Air		No hazard identified
Soil	510 mg/kg	Dry matter
Oral		Does not bioaccumulate.
Temporary use / release	1 mg/l	

Chlorobenzene

Compartment	Value	Remarks
Fresh water	0,032 mg/l	
Fresh water sediment	0,922 mg/kg	Dry matter
Marine water	0,0032 mg/l	
Marine sediment	0,0922 mg/kg	Dry matter
Sewage treatment plant	1,4 mg/l	
Soil	0,166 mg/kg	Dry matter

8.2 Exposure controls

General protection and hygiene measures:

Keep away from drinks, food and animal feedingstuffs. Remove contaminated, soaked clothing immediately. Wash hands before breaks and at the end of work. Avoid contact with eyes and skin. Do not breathe vapours or spray mist.

Respiratory protection:

Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter A2-P2 (EN529) is recommended.

Symptoms affecting the respiratory tract can also occur several hours after overexposure

Hand protection:

Conditionally suitable materials for protective gloves; EN 374:
Butyl rubber - IIR (≥ 0.5 mm); Break through time: ≥ 60 min
Recommendation: contaminated gloves should be disposed of.

Eye protection:

Wear eye/face protection.

Skin and body protection:

Wear suitable protective clothing. In case of hypersensitivity of the skin it is inadvisable to work with the product.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid at 20°C at 1.013 hPa	
Appearance:	Liquid	
Colour:	Yellow to brownish	
Odour:	Depending on solvent	
Odour threshold:	Not established	
pH:	Not applicable	
Melting point / boiling point:	approx. 77 °C at 1.013 hPa	
Flash point:	approx. -4 °C	DIN 51755
Evaporation rate:	Not established	
Flammability:	Not established	
Burning number:	Not established	

Upper/lower flammability or explosive limits:

Ethyl acetate	Upper: 11,5 %(V) / lower: 2,2 %(V)	
Chlorobenzene	Upper: 11,0 %(V) / lower: 1,3 %(V)	
Vapour pressure:	approx. 97 hPa at 20 °C	
Relative vapour density:	not established	
Density:	approx. 1,0 g/cm ³ at 20 °C	DIN 53217
Miscibility with water:	immiscible at 15 °C	
Water solubility	not established	

Wasserlöslichkeit von Inhaltsstoffen:

Ethyl acetate:	approx. 85 g/l	
Surface tension:	not established	
Distribution coefficient (n-Octanol/Water):	not established	
Auto-ignition-temperature:	not established	
Ignition temperature:	approx. 460 °C	
Decomposition temperature:	not established	
Heat of combustion:	not established	
Viscosity, dynamic:	approx. 3 mPa.s at 20 °C	DIN 53019
Viscosity, kinematic:	not established	
Flow time:	approx. 10 s	DIN 53221

9.2 Other information

The indicated values do not necessarily correspond to the product specification. Please refer to the technical information sheet for specification data.

Explosive properties:	not established
Dust explosion class:	not established
Oxidising properties:	not established

10. Stability and reactivity

10.1 Reactivity

This information is not available.

10.2 Chemical stability

No decomposition below initial boiling point.

10.3 Possibility of hazardous reactions

Exothermic reaction with amines and alcohols; reacts with water forming CO₂; in closed containers, risk of bursting owing to increase of pressure.

10.4 Conditions to avoid

This information is not available.

10.5 Incompatible materials

This information is not available.

10.6 Hazardous decomposition products

No hazardous decomposition products when stored and handled correctly.

11. Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity, oral

LD50 rat: > 2.000 mg/kg

Method: OECD Test Guideline 423

Toxicological studies at the product

Acute toxicity, dermal

Ethyl acetate

LD50 rabbit, male: > 18.000 mg/kg

Tris(p-isocyanatophenyl) thiophosphate

Based on available data, the classification criteria are not met.

Chlorobenzene

rabbit:

Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity, inhalation

Ethyl acetate

LC50 rat: > 22,5 mg/l, 6 h

Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhalation toxicity

Tris(p-isocyanatophenyl) thiophosphate

LC50 rat, male: 5,721 mg/l, 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Chlorobenzene

LC50 rat, male/female: 29,7 mg/l, 4 h

Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhalation toxicity

Method: OECD Test Guideline 403.

Assessment: Harmful if inhaled.

Regulation (EC) No 1272/2008

Primary skin irritation

Species: rabbit

Result: slight irritant

Classification: No skin irritation

Method: OECD Test Guideline 404

Toxicological studies at the product

Primary mucosae irritation

Species: rabbit

Result: slight irritant

Classification: No eye irritation

Method: OECD Test Guideline 405

Toxicological studies at the product

Sensitisation

Ethyl acetate

Skin sensitisation according to Magnusson/Kligmann (maximizing test):

Species: Guinea pig

Result: negative

Classification: Does not cause skin sensitization.

Method: OECD Test Guideline 406

Respiratory sensitization

No data available

Tris(p-isocyanatophenyl) thiophosphate

Skin sensitisation according to Buehler (epicutaneous test):

Species: Guinea pig

Result: negative

Classification: Does not cause skin sensitization.

Method: OECD Test Guideline 406

Toxicological studies at the product containing solvent.

Respiratory sensitization

Classification: No classification according to EC Directives 2006/121/EC or 1999/45/EC as respiratory sensitizer.

Chlorobenzene

Skin sensitisation:

Species: Guinea pig

Result: negative

Classification: Does not cause skin sensitization.

Respiratory sensitization

No data available.

Subacute, subchronic and prolonged toxicity

Ethyl acetate

LOAEL (Lowest observable adverse effect level): 350 ppm

Application Route: Inhalative

Species: rat, male/female

Dose Levels: 0 - 350 - 750 - 1500 ppm

Exposure duration: 13 w

Frequency of treatment: 6 hours a day, 5 days a week

Target Organs: Nasal inner lining

Test substance: vapour

Method: OECD Test Guideline 413

NOAEL: 900 mg/kg

Application Route: Oral

Species: rat, male/female

Dose Levels: 0 - 300 - 900 - 3600 mg/kg

Exposure duration: 13 w

Frequency of treatment: daily

Tris(p-isocyanatophenyl) thiophosphate

NOAEL: 2,8 mg/m³

Application Route: Inhalative

Species: rat, male/female

Dose Levels: 0 - 2,8 - 15,4 - 74 mg/m³

Exposure duration: 28 d

Frequency of treatment: (6 hours a day, 5 days a week)

Test substance: as aerosol

Method: OECD Test Guideline 412

Chlorobenzene

NOAEL: 125 mg/kg

Application Route: Oral

Species: rat, male/female

Subsequent observation period: 90-day

Method: OECD Test Guideline 408

NOAEL: 120 mg/kg

Application Route: Oral

Species: rat, male/female

Dose Levels: 0 - 60 - 120 mg/kg/day

Frequency of treatment: 5 days/week

Method: OECD Test Guideline 451

NOAEL: 234 mg/m³ air

Application Route: inhalation (vapour)

Species: rat, male/female

Frequency of treatment: 6 hours a day, 5 days a week

Carcinogenicity

Ethyl acetate

No data available.

Chlorobenzene

NOAEL (Toxicity): 120 mg/kg body weight/day

Species: rat, male/female

Application Route: Oral

Dose Levels: 0 - 60 - 120

Exposure duration: 103 week(s)

Frequency of treatment: 5 times/week

Method: OECD Test Guideline 451

Reproductive toxicity/Fertility**Ethyl acetate**

Available data show no indications for reproductive toxicity.

Tris(p-isocyanatophenyl) thiophosphate

Available data show no indications for reproductive toxicity.

Chlorobenzene

NOAEL - Parents: 450 ppm

NOAEL – F1: 450 ppm

NOAEL – F2: 450 ppm

Test type: Two-generation study

Species: rat, male/female

Application Route: Inhalative

Frequency of treatment: 6 hours/day 7 days/week

Reproductive toxicity/Developmental Toxicity/Teratogenicity**Ethyl acetate**

NOAEL (teratogenicity): 20000 ppm

NOAEL (maternal): 16000 ppm

NOAEL (developmental toxicity): 20000 ppm

Species: rat, female

Application Route: Inhalative

Dose Levels: 0 - 10000 - 16000 - 20000 ppm

Method: OECD Test Guideline 414

Studies of a comparable product.

Tris(p-isocyanatophenyl) thiophosphate

Available data show no indications for reproductive toxicity.

Chlorobenzene

NOAEL (teratogenicity): 590 ppm

NOAEL (maternal): 590 ppm

Species: rat, female

Application Route: Inhalative

Dose Levels: 75 - 210 - 590 ppm

Frequency of treatment: 6 hours/day (Exposure duration: 10 days (day 6 - 15 p.c.))

Method: OECD Test Guideline 414

Genotoxicity in vitro

Test type: Salmonella/microsome test (Ames test)

Result: No indication of mutagenic effects.

Method: OECD Test Guideline 471

Studies at the product

Test type: Point mutation in mammalian cells (HPRT test)

Test system: Chinese hamster V79 cell line

Metabolic activation: with/without

Result: negative

Method: OECD Test Guideline 476

Studies at the product.

Test type: Micronucleus test

Test system: Chinese hamster V79 cell line

Metabolic activation: with/without

Result: negative

Method: OECD Test Guideline 487

Studies at the product.

Genotoxicity in vivo**Ethyl acetate**

Test type: In vivo micronucleus test

Species: Mouse, male

Application Route: intraperitoneal

Dose: 0 -100 - 200 - 400 - 800 mg/kg

Result: negative

Method: OECD Test Guideline 474

Chlorobenzene

Test type: unscheduled DNA synthesis assay

Species: Mouse, female

Application Route: intraperitoneal

Result: negative

STOT evaluation – one-time exposure**Ethyl acetate**

May cause drowsiness or dizziness.

Tris(p-isocyanatophenyl) thiophosphate

Based on available data, the classification criteria are not met.

Chlorobenzene

Based on available data, the classification criteria are not met.

STOT evaluation – repeated exposure**Ethyl acetate**

Based on available data, the classification criteria are not met.

Tris(p-isocyanatophenyl) thiophosphate

Based on available data, the classification criteria are not met.

Chlorobenzene

Based on available data, the classification criteria are not met.

Aspiration toxicity**Ethyl acetate**

Based on available data, the classification criteria are not met.

Tris(p-isocyanatophenyl) thiophosphate

Based on available data, the classification criteria are not met.

Chlorobenzene

No data available.

CMR Assessment**Eethyl acetate**

Carcinogenicity: Based on available data, the classification criteria are not met.

Mutagenicity: In vitro an in vivo tests did not show mutagenic effects. On the basis of this data, the substance is not classified as mutagenic.

Teratogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity/Fertility: Based on available data, the classification criteria are not met.

Tris(p-isocyanatophenyl) thiophosphate

Carcinogenicity: Based on available data, the classification criteria are not met.

Mutagenicity: In vitro tests did not show mutagenic effects

Teratogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity/Fertility: Based on available data, the classification criteria are not met.

Chlorobenzene

Carcinogenicity: Based on available data, the classification criteria are not met.

Mutagenicity: Based on available data, the classification criteria are not met.

Teratogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity/Fertility: Based on available data, the classification criteria are not met.

Toxicology Assessment

Ethyl acetate

Acute effects: Causes serious eye irritation.

Sensitization: Based on available data, the classification criteria are not met.

Tris(p-isocyanatophenyl) thiophosphate

Acute effects: Harmful if swallowed.

Sensitization: Based on available data, the classification criteria are not met.

Repeated dose toxicity: Based on available data, the classification criteria are not met.

Chlorobenzene

Acute effects: Harmful if inhaled. Causes skin irritation.

Sensitization: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Other information

Special properties/effects: Over-exposure entails the risk of concentration-dependent irritating effects on eyes, nose throat, and respiratory tract. Delayed appearance of the complaints and development of hypersensitivity (difficult breathing, coughing, asthma) are possible. Hypersensitive persons may suffer from these effects even at low isocyanate concentrations, including concentrations below the occupational exposure limit. Prolonged contact with the skin may cause tanning and irritant effects.

Animal tests and other research indicate that skin contact with diisocyanates can play a role in causing isocyanate sensitization and respiratory reaction.

12. Ecological information

12.1 Toxicity

Acute Fish toxicity

Species: Danio rerio (zebra fish)

Exposure duration: 96 h

Method: OECD Test Guideline 203

No toxic effects with saturated solution.

Ecotoxicological studies of the product

Chronic Fish toxicity

Ethyl acetate

NOEC < 9,65 mg/l

Species: Pimephales promelas (fathead minnow)

Exposure duration: 32 d

Method: Early life stage test

Chlorobenzene

NOEC 4,8 mg/l
Test type: Early life stage test
Species: Danio rerio (zebra fish)
Exposure duration: 28 d
Method: OECD Test Guideline 210

Acute toxicity for daphnia

Species: Daphnia magna (Water flea)
Exposure duration: 48 h
Method: OECD Test Guideline 202
No toxic effects with saturated solution.
Ecotoxicological studies of the product

Chronic toxicity to daphnia**Ethyl acetate**

NOEC (Reproduction) 2,4 mg/l
Species: Daphnia magna (Water flea)
Exposure duration: 21 d

Chlorobenzene

NOEC 0,32 mg/l
Species: Daphnia (water flea)
Exposure duration: 16 d

Acute toxicity for algae

Species: scenedesmus subspicatus
Exposure duration: 72 h
Method: OECD Test Guideline 201
No toxic effects with saturated solution.
Ecotoxicological studies of the product

Acute bacterial toxicity

EC50 > 10.000 mg/l
Species: activated sludge
Method: OECD Test Guideline 209
Ecotoxicological studies of the product

Sediment Toxicity**Ethyl acetate**

Due to the low n-octanol-water partition coefficient, an adsorption on the sediment is not to be expected.

Ecotoxicology Assessment**Ethyl acetate**

Acute aquatic toxicity: The substance is graded as non-critical to water organisms.

Chronic aquatic toxicity: Due to easy biodegradability, the chronic aquatic toxicity can be regarded as uncritical.

Toxicity Data on Soil: Not expected to adsorb on soil.

Impact on Sewage Treatment: Because of the low bacterial toxicity, there is no risk of an adverse effect on the performance of biological waste water treatment plants.

Tris(p-isocyanatophenyl) thiophosphate

Acute aquatic toxicity: Based on available data, the classification criteria are not met.

Chronic aquatic toxicity: Based on available data, the classification criteria are not met.

Impact on Sewage Treatment: Because of the low bacterial toxicity, there is no risk of an adverse effect on the performance of biological waste water treatment plants

Chlorobenzene

Acute aquatic toxicity: Based on available data, the classification criteria are not met.

Chronic aquatic toxicity: Toxic to aquatic life with long lasting effects. Classification/labelling according to Regulation (EC) No. 1272/2008, Annex VI

12.2 Persistence and degradability**Biodegradability****Ethyl acetate**

Test type: aerobic

Inoculum: activated sludge

Biodegradation: ca. 69 %, 20 d, i.e. readily biodegradable

Inoculum: activated sludge

Biodegradation: 93 %, 6 d, i.e. readily biodegradable

Method: Simulation study

Tris(p-isocyanatophenyl) thiophosphate

Test type: aerobic

Inoculum: activated sludge

Biodegradation: 58,2 %, 28 d, i.e. not readily degradable

Method: OECD Test Guideline 301 F

Chlorobenzene

Biodegradation: 15 %, 28 d, i.e. not readily degradable

Method: OECD Test Guideline 301 F

Stability in water**Ethyl acetate**

Test type: Hydrolysis

Half life: 16 Years (pH: 5)

Hydrolytic temperature: 25 °C

Test type: Hydrolysis

Half life: 2 Years (pH: 7)

Hydrolytic temperature: 25 °C

Test type: Hydrolysis

Half life: 7,5 d (pH: 9)

Hydrolytic temperature: 25 °C

Hydrolyses slowly on contact with water.

Tris(p-isocyanatophenyl) thiophosphate

Test type: Hydrolysis

Half life: < 24 h at 20 °C (pH: 7)

Method: OECD Test Guideline 111

The substance hydrolyzes rapidly in water.

Studies of a comparable product.

Photodegradation

Ethyl acetate

Test type: Phototransformation in air

Temperature: 25 °C

Sensitizer: OH-radicals

Half-life indirect photolysis: 75 h

After evaporation or exposure to the air, the product will be slowly degraded by photochemical processes.

Chlorobenzene

Degradation (direct photolysis): 55 %

Degradation time (direct photolysis): 24 d

Volatility (Henry's Law constant)

Tris(p-isocyanatophenyl) thiophosphate

Calculated value = 0,621 Pa*m³/mol at 20 °C

The substance has to be scored as being slightly volatile from water.

Adsorbed organic bound halogens (AOX)

Chlorobenzene

The product contains organic halogens.

12.3 Bioaccumulative potential

Bioaccumulation

Ethyl acetate

Bioconcentration factor (BCF): 30

Species: *Leuciscus idus* (Golden orfe)

Exposure duration: 3 d

Does not significantly accumulate in organisms.

Chlorobenzene

Bioconcentration factor (BCF): 3,9 - 40

Partition coefficient (n-octanol/water)

Chlorobenzene

log Pow: 3

12.4 Mobility in soil

Distribution among environmental compartments

Ethyl acetate

Adsorption/Soil

Due to the low n-octanol-water partition coefficient, an adsorption on the soil is not to be expected.

Highly mobile in soils

Tris(p-isocyanatophenyl) thiophosphate

Adsorption/Soil

Koc value: 256000

Method: calculated

Environmental distribution

Ethyl acetate

Method: (calculated)

The product will be dispersed amongst the various environmental compartments (soil/ water/ air).



12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

No data available.

12.6 Other adverse effects

Isocyanate reacts with water at the interface forming CO₂ and a solid insoluble product with high melting point (polyurea). This reaction is accelerated by surfactants (e.g. detergents) or by watersoluble solvents. Previous experience shows that polyurea is inert and non-degradable.

13. Disposal considerations

Dispose in accordance with applicable international, national and local laws, ordinances and statutes. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

13.1 Waste treatment methods

After final product withdrawal, all residues must be removed from containers (drip-free, powder-free or paste-free). Packaging empty of usable product can be handed to a professional waste management company; in the EU, this is done per packaging type at collection points run by the existing take-back systems for the chemicals industry. The product and hazardous substance labelling must be left intact on the packaging.

Alternatively, the product and hazardous substance labelling can be removed if the product residues adhering to the sides are rendered non-hazardous. This packaging can also be handed to the collection points run by the existing take-back systems for the chemicals industry for packaging type-specific recycling. Containers must be recycled in compliance with national legislation and environmental regulations.

No disposal into waste water.

14. Transport information

ADR/RID

14.1 UN number or ID number	:	UN 1173
14.2 UN proper shipping name	:	ETHYL ACETATE, SOLUTION
14.3 Transport hazard class(es)	:	3
Hazard Identification Number	:	33
14.4 Packing group	:	II
14.5 Environmental hazards	:	no

Limited quantity regulations applicable in accordance with chapter 3.4 ADR/RID in compliance with threshold value.

ADN

14.1 UN number or ID number	:	UN 1173
14.2 UN proper shipping name	:	ETHYL ACETATE, SOLUTION
14.3 Transport hazard class(es)	:	3
Hazard Identification Number	:	33
14.4 Packing group	:	II
14.5 Environmental hazards	:	no

This classification data does not apply to transportation by tanker. If required, additional information can be requested from the manufacturer.

IATA

14.1 UN number or ID number	:	UN 1173
14.2 UN proper shipping name	:	ETHYL ACETATE, SOLUTION
14.3 Transport hazard class(es)	:	3
14.4 Packing group	:	II
14.5 Environmental hazards	:	no

IMDG

14.1 UN number or ID number	:	UN 1173
14.2 UN proper shipping name	:	ETHYL ACETATE, SOLUTION
14.3 Transport hazard class(es)	:	3
14.4 Packing group	:	II
14.5 Marine pollutant	:	no
EmS Code	:	F-E - S-D
Segregation Group IMDG	:	not applicable

14.6 Special precautions for user

See section 6 - 8.

Additional information	:	Highly flammable. Keep dry. Avoid heat above +40 °C. Keep away from foodstuffs, acids and alkalis.
------------------------	---	--

14.7 Maritime transport in bulk according to IMO instruments

Product is not transported by us in bulk

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances.

P5c Flammable liquids

Quantity1	:	5.000 t	Quantity2	:	50.000 t
-----------	---	---------	-----------	---	----------

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: 3, 40

This product contains substances subject to EU Regulation 1907/2006 (REACH), Annex XVII

Ethyl acetate

CAS-No.: 141-78-6, EC-No.: 205-500-4
Subject to REACH Annex XVII, No. 40

TA Luft List (Germany)

Type: Organic Substances
Portion Class 1: 27 %
Fraction of other substances: 73 %

Water contaminating class (Germany)

1 slightly water endangering
Classification according to AwSV, Annex 1 (5.2)

Any existing national regulations on the handling of isocyanates must be observed.

Products containing solvent:

Any existing national regulations on the handling of solvents must be observed.

Other regulations

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

Chemical Safety Assessment has been carried out for:

Ethyl acetate
Tris(p-isocyanatophenyl) thiophosphate
Chlorobenzene

16. Other information

1 Full text of the hazard statements of the CLP classification (1272/2008/CE) referred to under sections 2, 3 and 10.

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects

No annex is provided for this mixture, because the necessary information about operational conditions and Risk Management Measures (RMM) of the identified uses can be found in section 8 of this SDS

Abbreviations and acronyms

ADN	Accord européen relatif au transport international des marchandises Dangereuses par voie de Navigation intérieure
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route
ANSI	American National Standards Institute
ASTM	American Society of Testing and Materials (US)
ATE	Acute Toxic Estimate
AwSv	Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen
BCF	Bioconcentration Factor
CAS	Chemical Abstract Service
CLP	Regulation on Classification, Labelling and Packaging of Substances and Mixtures
CMR	Carcinogenic Mutagenic Reprotoxic
DIN	Deutsches Institut für Normung
DNEL	Derived No-Effect Level
EC...	Effect Concentration ... %
EWC	European Waste Catalogue
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LOAEL	Lowest Observable Adverse Effect Level
LC...	Lethal Concentration, ...%
LD...	Lethal Dose, ...%
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEL	No Observed Adverse Effect Level
NOEL/NOEC	No Observed Effect Level/Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire de marchandises Dangereuses
STOT	Specific Target Organ Toxicity
TRGS	Technische Regeln für Gefahrstoffe
vPvB	very Persistent, very Bioaccumulative
WGK	Wassergefährdungsklasse

Further information

Classification of the mixture:	Classification procedure:
Flam. Liq. 2 H225	Based on product data or assessment
STOT SE 3 H336	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text